

XTREME POWER CONVERSION J60

Lithium UPS // 120VAC or 208/230VAC

For more information, visit www.xpcc.com/j60



Protect A/V and automation systems from surges and power outages with ultra-slim J60 UPS

Xtreme Power J60 provides the benefits of lithium battery technology in a slim 1.2" form factor UPS. Integral mounting brackets, and easy access receptacles make J60 ideal for providing continuous power where a conventional UPS will not fit.

Lithium battery technology allows J60 to operate continuously at up to 40°C (104°F) without reduction in battery life.

J60's compact design is excellent for providing protection to automation systems, video walls, PoE Switches, programmable logic controller (PLC), kiosks, gaming machines, and point-of-sale (POS) equipment.

For a slim PDU with remote switchable receptacles, reference the J40S surge PDU at www.xpcc.com/j40

PRODUCT SNAPSHOT

- › 350VA/200W Capacity
- › Slim and light weight (1.2" and 3.4 lbs) the J60 mounts easily behind flat panel displays
- › Available 120VAC or 208/230VAC models
- › Power outage protection - over 6 minutes with 200W load
- › Rugged environments - perfect for high temperature and frequent power interruptions
- › 3 years electronics, 3 years battery warranty (USA and Canada)
- › J60i will be available Q3 2017

FEATURES

Long Life Battery—LiFePO4 batteries provide protection for up to 8 years and 2000 discharges

Input cord—optional detachable offset, right angle 5–15P power cord provides flat installations (J60 only)

Ease of use—plug-and-play functionality means the UPS is ready to start backing up your equipment right out of the box

Auto restart—after full battery discharge, the J60 automatically restarts when utility power returns

Battery Safety and Protection Protection Circuit Module prolongs life of J60 Li-ion batteries by protecting from overcharging/over-discharging

Flat installation—Input connector, output receptacles, and USB are located on J60 sides for flat installations


XTREME
Power Conversion®

Protect your business.

MODEL SELECTION GUIDE

For more information, visit www.xpcc.com/j60

MODEL NUMBER		J60-350	J60i-350 J60i will be available Q3 2017
CAPACITY	Power rating	350VA (200W)	
INPUT	Voltage	120VAC	208/230VAC
	Frequency	50/60Hz	
OUTPUT	Voltage	120VAC	208/230VAC
	Waveform	Sine wave (normal), simulated sine wave (battery mode)	
	Frequency	50/60Hz	
	Surge suppression	312 joules	
	Transfer time	2-6 min (typical)	
BATTERY	Battery type	Lithium Iron Phosphate (LiFePo4)	
	Battery quantity and size	(8) 18650 cells, 2400mAh	
	Battery runtime (est)	6 min at 100% load; 14 min at 50% load	
PHYSICAL	Dimensions (W x D x H)	6.9 x 8.5 x 1.25 in	
	Weight	3.4 lbs	
	Line cord	Detachable 5–15P to C13	C14 inlet
	Receptacles	(3) 5–15R	(2) IEC C13
ENVIRONMENT	Temperature	32–104°F (0–40°C)	
	Humidity	0–90%	
	Altitude	11,500 ft above sea level	
APPROVALS	UL-1778, cTUVus, FCC, and RoHS (J60 only)		
WARRANTY	3 years electronics, 3 years battery warranty (USA and Canada)		
COMMUNICATIONS INTERFACE	USB		
AVAILABLE OPTIONS	Optional offset right angle 5–15P 18" or 6 ft (J60 only)		
INCLUDED IN BOX	ViewPower CD, user manual, 5–15P to C13 line cord (J60 only)		



XTREME
Power Conversion®

Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

XPC EMEA / Rotterdam, NL / emea@xpcc.com

www.xpcc.com

©2017 Xtreme Power Conversion Corporation. All Rights Reserved. J60.02U (Rev 2/8/17)